

**Independent Leg Self Elevating Mobile Offshore Drilling Unit
Built 1987. Status: Currently Under Contract until NOV 2011**

----- [Travelling Equipment](#)

----- Block Oilwell A-500

----- [Rated Drilling Depth](#)

20,000 ft. with 5" drill pipe.

[Top Drive](#)

Varco IDS-1

[Leg Length](#)

404 ft.

[Rotary](#)

Oilwell B375, 37 1/2"

[Water Depth](#)

300 ft.

[Pumps](#)

3- Ideco 1600, 1600 hp
each powered by 2 GE 752 electric motors

[Hull Dimensions](#)

203 x 190x 22 ft.

[Well Control Equipment](#)

Regan 30" diverter system
500 psi.

[Drilling Envelope](#)

45 x 22 ft.

13 5/8" Shaffer annular preventer
5000 psi.

[Variable Loads](#)

Move 1322 M.Ton
Elevated 1500 M.Ton.

13 5/8" Shaffer single ram preventer
10,000 psi H2S trim

[Hook Load](#)

1,000,000 lbs.

13 5/8" Shaffer double ram preventer
10,000 psi H2S trim

Koomey Type 210-11S accumulator unit

[Storage](#)

Fuel 1994 bbls.
Drill water 8492 bbls.
Potable water 2336 bbls.
Liquid mud 1580 bbls.
Bulk 7200 cu. ft.
Sack storage 1800 sck.

[Rig Supply Power](#)

4 Caterpillar 3516, 1855 HP each powering
a caterpillar SR4B generator 1240 KVA
Ross Hill SCR system Model 1400

[Rotary Load](#)

900,000 lbs.

[Cranes](#)

1-Monarch Seatrax Model 6024
70 ton capacity with a 130 feet boom
1-Seatrax Series 42 Model 4220
46 ton capacity with a 100 feet boom
1 Seatrax series 42 type E rated to 25
Tons

[Set Back Load](#)

500,000 lbs.

[Derrick](#)

Dreco Deminsions 147x30x30 feet

[Drill String](#)

5" grade G drill pipe
5" HWDP
6 1/2" drill collars
8 1/4" drill collars

[Drawworks](#)

Ideco ES 2100 2000 HP
1 3/8" drill line
powered by 2 GE 752 electric motors

[Safety Equipment](#)

As required by regulations

[Auxiliary Brake](#)

Baylor Model 7838 electric brake

[Quarters](#)

To accommodate 88 persons